

- Sikret mot polvending og overspenning. 6,3 A sikring (inngang)
- Termisk sikret, kortslutningssikker og overspenningsbeskyttet ved ca. 16 V (utgang)
- 6,3 mm flatstiftkontakter (inngang og utgang)
- Spesielt beregnet for mobiltelefoner
- "E"-merket for kjøretøy direktivet (95/54/EC)
- Protected against reversed polarity and overvoltage. 6,3 A fuse (input)
- Thermal protection, short circuit proof and overvoltage protection at approx. 16 V (output)
- 6,3 mm push-on terminals (input and output)
- Specially designed for mobile telephones
- "E"-marked vehicle directive ref. (95/54/EC)



Tekniske data		Technical specifications	
Inngangsspenning:		Input voltage:	22-32 VDC
Utgangsspenning:		Output voltage:	13,3 VDC
Maks. utgangseffekt:		Max. output power:	75 W
Laststrøm:		Load current:	6,0 A
Lastregulering (0-6,0 A last og 24 VDC inngangsspenning):		Load regulation (0-6,0 A load and 24 VDC input voltage):	< 3,0%
Linjeregulering (22-32 V inngangsspenning og 6 A last):		Line regulation (22-32 V input voltage and 6 A load):	< 2,0%
Svitsjefrekvens ca.:		Switch frequency approx.:	30 kHz
Tomgangsstrøm ca.:		No load current approx.:	35 mA
Temperaturområde:		Temperature range:	-20°C - +40°C
Rippel (6 A last og 28 V inngangsspenning):		Ripple (6 A load and 28 V input voltage):	3 mV RMS
Virkningsgrad:		Efficiency:	80%
EMC standarder		EMC standards	
• Emisjon:		• Emission:	EN 61000-6-3,95/54/EC
• Immunitet:		• Immunity:	EN 61000-6-1,95/54/EC
Mål (LxBxH):		Dimensions (LxWxH):	96 x 115 x 38 mm
Vekt:		Weight:	400 g